

RECHARGEABLE

INTRANT™ DUAL-LIGHT™ ANGLE LIGHT



HEAD ROTATES 90°

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT

GRAB-N-GO
CHARGING BASE



Head rotates 90° - directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches independently control separate LEDs



Heavy-duty, clip and V-ring securely holds tight to gear in any situation

| FL1 STANDARD | FLASH | FLOOD | DUAL-LIGHT |
|--------------|------------|------------|------------|
| | 200 LUMENS | 100 LUMENS | 205 LUMENS |
| | 7h | 7h | 7h |
| | 401m | | |
| | 40256cd | | |
| | | | |

AVAILABLE IN MULTIPLE COLORS.



200 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

X-SERIES™

DUAL-LIGHT™ ANGLE LIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2
 XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8
 XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, Atex, IECEx, INMETRO, Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY

- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 12VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

| FL 1 STANDARD | FLASH | FLOOD | DUAL-LIGHT |
|---------------|------------|------------|------------|
| | 200 LUMENS | 100 LUMENS | 205 LUMENS |
| | 7h | 7h | 7h |
| | 401m | | |
| | 40256cd | | |
| | | | |
| | | | |

Bayco Products, Inc. XPR-5568
 640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 For use with Bayco Li-ion Battery Pack 5568-BATT or 5566-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only

UL LISTED
 E 467756
 ID 4003544
 ELECTRICAL SAFETY
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE
 CE 2575
 Control Drawing: 5568-CERT-DWG1-03

CLASSIFICATION
 CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV 1 GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia IIC T4 Ga
 Ⓢ I M1 Ex ia op is I Ma
 Ⓢ II 1 G Ex ia op is IIC T4 Ga

Ex ia op is I Ma
 Ex ia op is IIC T4 Ga
 DEMKO 17 ATEX 1927
 IECEx UL 17.0082
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell Alkaline
 3.7V/Cell Li-ion
 IP-67
 Um: 10V

SEQUENCE

CERTIFIED

AVAILABLE IN MULTIPLE COLORS.

© 2020 Bayco Products, Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPR-5568-20

