



- 3 brightness levels plus strobe
- Adjustable ratchet tilt head
- Adjustable elastic head strap
- Impact and chemical resistant

# **1,000**LUMENS

## USB 4708B

Woodway Engineering Ltd Lower Road, Barnacle Coventry, CV7 9LD United Kingdom Tel: +44 (0) 24 76 841750 Fax: +44 (0) 24 76 621796 sales@woodwayengineering.com www.woodwayengineering.com





#### **PRODUCT SPECIFICATION SHEET**

# Adjustable Beam Headlamp

## **USB Rechargeable**

### USB-4708B



## INCLUDED

- USB cable and micro USB cable
- Lithium-ion Rechargeable Battery

## **SPECIFICATIONS**

- Floodlight Lumens: High 1,000, Medium 600 Lumens, Low 250 Lumens
- Floodlight Run-time: High 2.25, Medium 3.25, Low 6.25
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7 in., Head Diameter: 1.8 in., Handle Diameter: 1 x 1.3 in., Weight: 6.1 oz.

FL1 STANDARD	FLOOD HIGH	FLOOD MEDIUM	FLOOD LOW
342	1000 LUMENS	600 LUMENS	250 LUMENS
	2h 15min	3h 15min	6h 15min
2m			
1m	CE		

## FEATURES

- CREE<sup>®</sup> LED technology 50,000 + hours LED
- 3 brightness levels plus strobe
- Aircraft-grade 6061-T6 aluminum housing
- Type III hard anodized finish
- Single switch located on side of the light
- Adjustable ratchet tilt head
- Adjustable elastic head strap
- IP-X7 Waterproof
- Impact and chemical resistant
- Powered by a rechargeable Li-ion battery
- Limited Lifetime Warranty

ch loc ratch elasti rproc cher y a re etime

Woodway Engineering Ltd Lower Road, Barnacle Coventry, CV7 9LD United Kingdom

Tel: +44 (0) 24 76 841750 Fax: +44 (0) 24 76 621796 sales@woodwayengineering.com www.woodwayengineering.com