

LI-ION RECHARGEABLE

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

XPR-5582RX  
XPR-5582GX

# NIGHTSTICK®

Life Depends on Light™

**1750**

**POWERFUL LUMENS**

INCLUDING HIGH & LOW



**Rear green safety lights** provide visibility in smoke filled applications



**Carry strap with seat belt style buckle** for additional hands-free use



**Convenient locking snap-in charger** included



Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment



AVAILABLE IN MULTIPLE COLORS



FL1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
	2m	1m

**1750 LUMENS**

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

**INTRINSICALLY SAFE**

**PRODUCT SPECIFICATION SHEET**

**INTEGRITAS™**

# LANTERN

**LI-ION RECHARGEABLE**

## ITEM NUMBER/UPC

XPR-5582RX (Red), UPC# 0 17398 806824  
XPR-5582GX (Green), UPC# 0 17398 807029

## MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

## CERTIFICATIONS

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position  
- US Patent 9,713,217

## CASE MATERIAL

- Glass filled nylon polymer

## LUMENS/RUNTIME

### FLASHLIGHT

- HIGH: 1750L, 5 hrs. runtime  
- LOW: 600L, 11 hrs. runtime

## CANDELA

### FLASHLIGHT

- HIGH: 81,250  
- LOW: 27,083

## BEAM DISTANCE

### FLASHLIGHT

- HIGH: 552m  
- LOW: 325m

## WATER RATING

- IP-67 (dustproof and waterproof)

## DROP RATING

- 2 meters

## DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm  
- WIDTH: 4.26 in / 10.8 cm  
- DEPTH: 5.83 in / 14.8 cm  
- WEIGHT: 2 lbs. 11 oz. / 1219 g

## BATTERY







- Rechargeable Li-ion battery pack

## WARRANTY

- Limited lifetime warranty

## WHAT'S INCLUDED

- Lantern  
- Li-ion rechargeable battery pack  
- Locking snap-in charger (5582-CHGR1)  
- AC power supply  
- DC direct wire kit with in-line fuse  
- Removable shoulder strap  
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	<b>1750 LUMENS</b>	<b>600 LUMENS</b>
	<b>5h</b>	<b>11h</b>
	<b>552m</b>	<b>325m</b>
	<b>81250cd</b>	<b>27083cd</b>
	<b>2m</b>	
	<b>1m</b>	



**Bayco Products, Inc. XPR-5582**  
640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

CLASS I DIV 2 GRPS A-D T3  
CLASS II & III DIV 2 GRPS F-G T135°C  
CLASS I ZONE 2 Group IIC T3  
-20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.  
AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.  
WARNING: Risk of ignition - Do not charge batteries in a hazardous area.  
AVERTISSEMENT: Danger d'inflammation - Ne pas charger les piles dans une zone dangereuse.

**CERTIFIED**



AVAILABLE IN MULTIPLE COLORS