

LI-ION RECHARGEABLE

XPR-5592GCX

INTRINSICALLY SAFE SCENE LIGHT

# NIGHTSTICK®

Life Depends on Light™

## MAGNETIC MOUNT

Non-marring rubber covered base positions light for **360° rotation** and **holds firm**.



**Steel-reinforced carry handle** also functions as convenient mounting hook where needed.



**Locking cam** allows carry handle to telescope to ideal length and position.



**Large adjustment knobs** means light can be positioned and secured for hands-free work.



**Sealed switch and charging port cap** ensure full IP-67 waterproof & dust-proof protection.



6 foot tripod and blow-molded case included.

## 1200 LUMENS

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

**INTRINSICALLY SAFE**

# SCENE LIGHT

**LI-ION RECHARGEABLE**
**ITEM NUMBER/UPC**

XPR-5592GCX - 017398807012

**CERTIFICATIONS**

- ATEX
- IECEx
- CE
- BC
- cULus
- Meets requirements of NFPA 1971-8.6 (2013)

**CASE MATERIAL**

- Glass-filled nylon polymer
- Serialized for personal identification

**LUMENS/RUNTIME**

- HIGH: 1200L, 6 hrs. runtime
- LOW: 650L, 12 hrs. runtime

**WATER RATING**

- IP-67 (dust-proof, waterproof)

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 13.5 in (343mm)
- WIDTH: 9.25 (235mm)
- DEPTH: 3.5 in (89mm)
- WEIGHT: 4 lbs 4 oz (1,928g)

**BATTERY**

- Integrated rechargeable li-ion battery

**WARRANTY**

- 1 Year limited warranty

**PATENTED**

- US PATENT 10,879,519

**WHAT'S INCLUDED**

XPR-5592GX

- Scene Light
- AC & DC charging cords
- Blow-molded case

XPR-5592GCX

- Scene Light
- 6 foot tripod
- AC & DC charging cords
- Blow-molded case


**Bayco Products, Inc.**  
 640 S. Sanden Blvd., Wylie, TX 75098

**LISTED**

E 467756

ID 4003544

ELECTRICAL SAFETY

INTRINSICALLY SAFE

SECURITE INTRINSEQUE

FLOODLIGHT FOR USE IN HAZARDOUS LOCATIONS

For use with Bayco Li-Ion Battery Pack 5592-BATT only

CLASS I DIV 1 GRPS A-D T4 DEMKO 19ATEX 2169

CLASS II &amp; III DIV1 GRPS E-G T135°C IECEx UL 19.0013

CLASS I ZONE 0 GROUP IIC T4 Ga -20°C ≤ Tamb ≤ +40°C

@II 1G Ex ia op is IIC T4 Ga 5592-BATT

Ex ia op is IIC T4 Ga 3.7V/Cell Li-Ion

Um 10V

WARNING: Do not charge battery in a hazardous location

WARNING: Do not replace battery when an explosive atmosphere is present

CE 2575 SEE INSTRUCTION MANUAL US Patent 10,879,519

VOIR MANUEL MFG MM-YY

Meets Requirements of NFPA-1971-8.6 (2013)


**CERTIFIED**


NFPA

