


Ø 820 mm

Tolerance: ±10 mm

300 W







DIMENSIONS \_\_\_\_\_ TECHNICAL DATA \_\_\_\_\_

General

Voltage Frequency

Operating Amperage Power Consumption (±5%)

Lamp+Tripod Lamp

Panel Power Consumption (±5%) Panel Luminous Flux (±10%) Correlated Color Temperature

Width Height

Weight Tripod Height (min-max)

Weight

Collapsed Height Collapsed Width

300 W

AC 100-240 V 50/60 Hz 1.5 A/3.1 A

150 W/300 W 15.8 kg

130 W/260 W 25,000 lm/50,000 lm

5,000 K 820 mm 630 mm 8.4 kg

1450-2180 mm

7.4 kg 1340 mm 180 mm

## **ACCESSORIES**

The MIDI LED Balloon Light standard package includes:

- LED Light System
- Omni Light Cover
- Medium Tripod
- Light Carry Bag
- Medium Tripod Carry Bag



**LIGHT CARRY BAG** 





MEDIUM TRIPOD CARRY BAG



## 2.8 M HEIGHT Distance 21 m 4 m 8 m 300 W 1385 m<sup>2</sup> Area $3 \text{ m}^2$ 50 m<sup>2</sup> 200 m<sup>2</sup> 0° PANEL ANGLE 0.5 lx **OMNI** COVER Full Light 100 lx Half Light 203 lx 50 lx 10 lx 0.5 lx

## **CUSTOMIZATION**

Our MIDI LED Balloon Light can also be customized with:

- Trolley Mount
- Light Cover
- RGB Light
- Fog Light
- Timer
- Custom Color Temperature
- Dimmer
- Remote Control / APP



Fax: +44 (0) 24 76 621796 sales@woodwayengineering.com www.woodwayengineering.com